

COMPACTCUT 201

LISSMAC
CONSTRUCTION TECHNOLOGY

IDEALLY SUITED FOR SMALL AND MEDIUM SIZED REPAIR WORKS
IN ASPHALT AND CONCRETE

- Floor saw in robust and compact construction
- The smooth raising and lowering of the saw blade with a closed threaded spindle prevents damaging of the saw blade
- Adjustable cutting depth indicator for all saw blade diameters
- A large water tank reduces work interruptions
- The water cooling system provides an optimum saw blade cooling, this guarantees a longer saw blade life
- Blade guard easily foldable
- Simple service operations - good access to engine and cutting shaft
- With a parking brake
- Height adjustable handles for ergonomic operation



TECHNICAL DATA	COMPACTCUT 201 P
cutting depth max.	200 mm
cutting depth setting	stepless threaded spindle with depth gauge
saw blade Ø max.	500 mm
saw blade holder	25.4 mm
drive motor	Honda petrol 1-cylinder
output power max.	8.7 kW, 11.8 hp
saw blade speed	2500 1/min.
dimensions (L/W/H)	1100/620/1020 mm
weight	108 kg

DIAMOND TOOLS RECOMMENDATION

Asphalt	ASW 11
Concrete	BSW 12

FLOOR SAWS

COMPACTCUT 201 P without diamond blade, incl. blade guard 500 mm

NR.

1061483