

DTS 600

LISSMAC
CONSTRUCTION TECHNOLOGY

SOLID MASONRY SAWS
FOR UNIVERSAL CONSTRUCTION JOB SITE USE

- The LISSMAC water spraying system guarantees optimum saw blade cooling and immediate removal of debris with very low water consumption and follows to the current safety regulation
- Table saw with stationary cutting head
- High quality maintenance-free design
- Welded steel construction and powder-coated water tank with exact table support for precise stone cuts
- Galvanised, foldable table legs for quick and compact transport
- Standard wheel set simplifies moving on the building site and loading in a vehicle
- With roller table equipped with safety catch and locking mechanism
- Integrated water pump transport lock
- Best transport option by using flexible (back/front) rubber handles
- Exact, smooth running cutting table with adjustable rip guide
- Simple saw blade change via removable saw hood cover



TECHNICAL DATA	DTS 600
cutting depth standard/max.	150 / 220 mm
cutting length	800 mm
saw blade Ø standard/max.	450 / 600 mm
saw blade holder	25.4 mm
output power max.	3.6 kW
voltage	400 V
saw blade speed	1400 1/min.
protection class	IP 54
dimensions (L/W/H)	1600/800/1600 mm
weight	94,6 kg

DIAMOND TOOLS RECOMMENDATION

Concrete	TL BETON LASER
----------	----------------

MASONRY SAWS

DTS 600 incl. diamond blade Ø 600 mm for concrete, natural stone

NR.

700502