

THE COMPACT DIAMOND CORE DRILLING MACHINES FOR WET AND DRY DRILLING

- Compact, lightweight and ergonomic design
- Three gear levels permit optimum speed selection adapted to the specific core drill diameter
- Simple, controlled operation during hand-guided core drilling using variable mountable clamping handle
- Simple, controlled operation during hand-guided core drilling using variable mountable clamping handle

MULTI-TRONIC

- Overload protection for the highest possible operating comfort and long service life
- Maximum safety due to electronic and mechanical overload coupling as well as additional thermal overload protection



CDM 20 P



[1] CDM 20 S wet/dry



[2] Antifriction washer



[3] Centre spike

TECHNISCHE DATEN	CDM 20 P	CDM 20 P, 110 V	CDM 20 S
rated power	2000 W	2000 W	2000 W
output power	1375 W	1300 W	1375 W
voltage	230 V/50-60 Hz	110 V/50-60 Hz	230 V/50-60 Hz
rated current	9.5 A	19 A	9.5 A
speed without load	670/1450/2770 1/min.	670/1450/2770 1/min.	670/1450/2770 1/min.
speed fully load	450/1050/2000 1/min.	435/1015/1935 1/min.	450/1050/2000 1/min.
core drill Ø masonry max.	200 mm	200 mm	200 mm
core drill Ø concrete max.	150 mm	150 mm	150 mm
core bit connection	1 1/4" UNC	1 1/4" UNC	1 1/4" UNC
clamping collar Ø	60 mm	60 mm	60 mm
dimensions (L/W/H)	468/106/297 mm	468/106/297 mm	564/106/164 mm
weight	7.5 kg	7,5 kg	7.5 kg

CORE DRILL MOTORS 230 V	NR.
CDM 20 P wet/dry, incl. carry case	1004139
[1] CDM 20 S wet/dry, incl. carry case	1004304
CORE DRILL MOTORS 110 V	NR.
CDM 20 P wet/dry, incl. carry case	1004229
ACCESSORIES	NR.
[2] CDM 20 - antifriction washer (brass)	823520
[3] CDM 20 - centre spike 190 - 250mm	700353
[3] CDM 20 - centre spike 230 - 350 mm	700354
[3] CDM 20 - centre spike 360 - 480 mm	700355
CDM 20 - adapter cable 2m plug Schuko I coupl. CEE 3-pin 16 A	822312
CDM 20 - adapter cable 2m plug CH Typ12 I coupl. Schuko	822311
CDM 20 - adapter cable 2m plug CEE 3-pin 16 A I coupl. Schuko	822310

