

# **P44 EVO** 3-PHASE




DIMENSIONS (Cm)	<u>Effective</u> 105 x 95 x h.89				
	On Pallet 105 x 95 x h.96				
WEIGHT (Kg)	Effective 500				
	On Pallet 510				
OIL	SAE = 40 $Quantity = 13  lt.$				
ELECTRIC MOTOR	400V - 50HZ 4 HP - 3 kW				
RPM	6				

Bending capability	$R. = 65 \text{ Kg.} / \text{mm}^2$			$R. = 85 \text{ Kg.} / \text{mm}^2$		
	1 Ø 38	2 Ø 30	3 Ø 24	1 Ø 36	2 Ø 28	3 Ø 22

### STANDARD EQUIPMENT

## BIGGER ROTATING PLATE: DIMENSION Ø 460 mm:



It can support bushes up to Ø 260 mm to realize bending of big radius without need of extra equipments (Special Arm for large radii).



- 1 hardened square pin; 1 hardened stirrup bending pin;
- 3 hardened bush holding pins; 1 checking block; 1 pedal;
- 7 bushes Ø50-60-70-80-95-120-150mm; 1 set Allen keys.
- 2 Long Saddles, indispensable to realize the "double bend"!

#### **OPTIONALS**



bend stirrups more simultaneously and determine the length from the bending point.



Spirals/Hoops Device:

Allows to realize spiral/hoop armatures with bars Ø max.16



'Basic Angle Control'' Panel:

Allows to set up manually 6 bending angles, that will be carried out in sequence.



"Angle Control" Panel:

This special computer permits to program up to 20 bending angles in very rapid and intuitive



# 2-Speed Motor:

Available on request for those who work bars of different diameters and want to optimize production times.



Special Bushes for large radii.



Working top "Type B": The cover in sheet metal prevents the turning plate from dust and material residuals.



#### Roller Bench:

o deposit and move the material. Available in different lengths, as needed.

MILANO – ITALY
Tel.: +39.2.90.93.97.35 – E-mail: info@simpedil.it