

BENDING MACHINES

P54 EVO 3-PHASE

DIMENSIONS (Cm) Effective 105 x 95 x h.89 On Pallet 105 x 95 x h.11 WEIGHT (Kg) Effective 585 On Pallet 600 OIL Quantity = 13 lt. Quantity = 13 lt. 400V - 50HZ ELECTRIC MOTOR 5,5 HP - 4 kW RPM 6 Standard 20 34 3 Ø 28 1 Ø 40 2 Ø 32 3 Standard Equipment Standard Equipment	
WEIGHT (Kg) 585 On Pallet 600OILSAE = 40 Quantity = 13 lt.Provide the second sec	
SAE = 40 Quantity = 13 lt.OILSAE = 40 Quantity = 13 lt.ELECTRIC MOTOR $400V - 50HZ$ $5,5 HP - 4 kWRPM6Bending capabilityR. = 65 Kg. / mm²1 Ø 442 Ø 343 Ø 281 Ø 402 Ø 323STANDARD EQUIPMENT$	
ELECTRIC MOTOR $5,5 \text{ HP} - 4 \text{ kW}$ RPM 6 Bending capability R. = 65 Kg. / mm ² R. = 85 Kg. / mm ² $1 \ \emptyset \ 44$ $2 \ \emptyset \ 34$ $3 \ \emptyset \ 28$ $1 \ \emptyset \ 40$ $2 \ \emptyset \ 32$ $3 \ \emptyset \ 32$ STANDARD EQUIPMENT	
I Ø 44 I Ø 44 I Ø 44 I Ø 40 I Ø 40 <thi 40<="" th="" ø=""> <thi 40<="" th="" ø=""> <thi 40<="" td="" th<="" ø=""><th></th></thi></thi></thi>	
	3 Ø 24
BIGGER ROTATING PLATE: DIMENSION Ø 550 mm:	
It can support bushes up to Ø 320 mm to realize bending of big radius without need of extra equipments (Special Arm for large radii).	pedal; len keys .
OPTIONALS	
"UNIQUE 2 in 1" To bend more stirrups simultaneously and determine the length from the bending 	rogram up to d intuitive
2-Speed Motor: Available on request for those who work bars of different diameters and want to optimize production times.	
BANCO BASE B A B C B A B C B A B C B C B C C B C C C C C C C C C C C C	

