

P56 EVO 3-phase

| | DIMENSIONS (Cm) | Effective 130 x 95 x h.89 On Pallet 130 x 95 x h.104 |
|---|--|---|
| | WEIGHT (Kg) | Effective 710 On Pallet 725 |
| | OIL | SAE = 40 Quantity = 13 lt. |
| | ELECTRIC MOTO | 400V - 50HZ 7,5 HP – 5,5 kW |
| • | RPM | 5 |
| Bending capability | R. = 65 Kg. / mm ² \emptyset 46 2 \emptyset 36 3 \emptyset 30 | R. = 85 Kg. / mm ² $1 \emptyset 42$ $2 \emptyset 34$ $3 \emptyset 26$ |
| STANDARD EQUIPMENT | | |
| BIGGER ROTATING PLATE: DIMENSION | rending of big radius or large radii). | vin; 1 hardened stirrup bending pin; lding pins; 1 checking block; 1 pedal; h95-120-150-175mm; 1 set Allen keys |
| 04 Long Saddles, indispensable to realize the " | double bend''! / bushes Ø60-70-80 |)-95-120-150-175mm; 1 set Allen keys. |
| | OPTIONALS | |



To bend more stirrups simultaneously and determine the length from the bending point.



Allows to realize spiral/hoop

armatures with bars Ø max.16



"Basic Angle Control" Panel: Allows to set up manually 6 bending angles, that will be carried out in sequence.



"Angle Control" Panel: This special computer permits to program up to 20 bending angles in very rapid and intuitive way.



Working top "Type B": The cover in sheet metal prevents the turning plate from dust and material residuals.



Available on request for those who work bars of

different diameters and want to optimize production

2-Speed Motor:

mm.

Roller Bench:

Special Bushes for large radii.

To deposit and move the material. Available in different lengths, as needed.

